

Nimo

The anywhere, anytime machine



Now concrete can be transported anywhere, anytime!!!

Presenting the Nimo, the anytime, anywhere mixer. This revolutionary product is the only mixer which is permitted to transport concrete during peak hours in the city.



Nimo in Tunnel application

Zoom to the site!

This mixer is mountable on any truck with a wheelbase of 3200mm. This small mixer can move far quicker through the heavy traffic prevalent in cities.

Technical Data

Truck Mixer Model	Unit	AM 3 SH
Nominal Filling Capacity	Litre (m ³)	3000 (3)
Total Geometric Volume	Lit	6350
Water Line Volume	Lit	3450
Filling Ratio	%	47
Primeover Power	KW	28
Drum speed	RPM	0-12
Water Tank	Litres	300
Oil contents of Gear Box	Litres (App)	7.5
Oil contents of hydraulic system	Litres (App)	19
Overall Length of Mixer	mm	4600
Width of Mixer	mm	2100
Height of Standard feed hopper	mm	2440
Standard height for driving	mm	3400
Size of mixer frame	mm	150 X 75 X 6
Weight of mixer standard	Approx. T	3.4
Weight of the concrete	t	7.2
Gross vehicle weight rating D	t	10
Weight of mixer accessories (Extension chute with support, ladder, fixtures)	kg	50

Constant concreting!

Concrete on the go is a key factor today that has helped the RMC industry evolve. Transit mixers are the most visible among the range of concreting equipment. But the common 6 m³ class Transit Mixers are not being allowed to ply inside city roads during the peak hours. It is because the Transit Mixers are offered on 16 tonner & higher capacity trucks which is classified as HCVs.

Schwing Stetter's Nimo, a 3 m³ Transit Mixers mounted on a 10 tonner truck (with 8.25 X 20 tyres) comes under the LCV category. Thus enables a continuous concreting.

Nimo is also ideal for delivering small loads of concrete to sites where it is not economically viable to send a larger mixer. Due to small size, Nimo can easily enter narrow roads, provide effortless movement on gradients and hilly terrain with sharp bends to deliver concrete. So if you want a quick moving mixer that can deliver concrete anywhere, anytime, the Nimo is the product for you.

Contact us in the numbers/email ids given below or contact your Schwing Stetter representative for further details.



SCHWING STETTER (INDIA) PVT LTD

ISO 9001:2008 :: OHSAS 18001: 2007 :: ISO 14001:2004

F 71 - 72, SIPCOT Industrial Park, Irungattukottai, Sriperumpudur Taluk, Kancheepuram District, Tamil Nadu - 602105.
Tel : 044 2715 6780 / 781, 47108100 Fax : 044 2715 6539 Email : schwing@vsnl.com, chennai@schwingstetterindia.com

MUMBAI | NEW DELHI | HYDERABAD | BANGALORE | KOLKATA | AHMEDABAD | PUNE | VIZAG | MANGALORE
COCHIN | MOHALI | BHUBANESWAR | GUWAHATI | RAIPUR | JAMSHEDPUR | COIMBATORE | SURAT | PATNA